

The Leaders in Portable X-Ray Systems



The most experienced team, In-House Research and Development, innovative technology, superb raw materials, we offer the best in every class:



Image Quality




Reliability




Ease of Use



Professional Support









Urban System



Detector

- Lightest in the Market
- Unmatched Image Quality

Detector Model	NOVO 15WS	
Steel Penetration *	3.5" (90mm)	-
Detector Weight	3.5 lbs. (1.6kg)	N®VO
Detector Load Proof	661 lbs. (300kg)	\$
Detector Imaging Area	9.1" x 11.2" (23.1cm x 28.4cm)	Đ
Detector Size	10.6" x 13" (26.9cm x 33cm)	
Active Area (Imaging Area / Detector Size)	74% Active Area	
Detector Drop Test	39.4" (100cm)	
Detector Thickness	0.6" (15.6mm)	
Bit Depth	16 bit latest generation	NOVO 15WS 3.5 lbs. (1.6kg)
Connector	Titanium Magnetic Dual Direction Connector	

^{*} Tested with Golden XRS-3 at ~10" (25cm)

Components

Spark III

- o.7 lbs. (0.3kg)
- 6 Hours built-in battery operation
- Wireless Up to 400m Line of Sight
- Supports All Golden Sources
- Quick connection to source
- MIL-DTL 38999 connectors
- Weatherproof design
- LED Indications
- Supports Golden On/Off & battery status info







Tablets (Most popular)







	Panasonic Toughbook® CF-33	Panasonic Toughpad™ FZ-G1	Samsung S20
Screen Size	12"	10.1"	6.2"
Screen Resolution	2160x1440	1920x1200	3200x1440
Screen Brightness (NIT)	1200	800	800
Touch Screen	\checkmark	\checkmark	✓
Operating System	Windows 10	Windows 10	Android

^{*}Additional tablets and laptops supported



	Litex	XR150	XR200	XRS-3	XRS-4
KVP	120	150	150	270	370
Weight	5.6 lbs.(2.5kg)	5.9 lbs. (2.7 kg)	10.7 lbs. (4.8 kg)	11.8 lbs. (5.3 kg)	18.3 lbs. (8.3 kg)
Size	11.7" x 3.2" x 4.7" (29.9cm x 8.2cm x 12cm)	10.4" x 3.5" x 4.7" (26.6cm x 9cm x 12.1cm)	10.7" x 4.3" x 5.8" (27.2cm x 10.8cmx 14.8cm)	14.2" x 4.3" x 5.8" (36.1cm x 10.9cm x 14.8cm)	19.3" x 4.8" x 7.1" (48.9cm x 12.2cmx 17.9cm)

3D ARC

3D Imaging with exact X, Y, Z measurements



Folding Slider L

Ideal for screening large objects



Folding Slider XXL

Super sized, ideal for screening XXL objects



Eagle

Extremely long range wireless transceiver up to 3 3km (2 miles) LOS



Extension Cables

Available at 50m, 100m and 150m for a total of 300m



Armor

Additional mechanical protection to the Detectors





Soft Protective Cover

Additional weather & impact protection



Tripod Mount

Firmly holds the detector and provides various positioning options





Lookout

Organic detection, live Video & Audio




Robot C-Arm

Detector and X-Ray Holder



Robot Detector Frame

Lightweight, shock absorbing



Wireless Super Ranger

Increases wireless distance and stability





Compatible with the XTK® Software



Contract # GS-07F-163DA